

10/19/2

DIALOG(R)File 347:JAPIO

(c) 2003 JPO & JAPIO. All rts. reserv.

06306407      \*\*Image available\*\*

ROTARY SEAL MECHANISM OF ROLL NECK PART

PUB. NO.:        11-248004 [JP 11248004 A]  
PUBLISHED:      September 14, 1999 (19990914)  
INVENTOR(s):    UEDA SOUICHIROU  
                  EDANE SATOSHI  
APPLICANT(s):   MUTSUBISHI RUBBER KK  
APPL. NO.:      10-066031 [JP 9866031]  
FILED:          March 03, 1998 (19980303)  
INTL CLASS:     F16J-015/32 ; B21B-031/07

ABSTRACT

PROBLEM TO BE SOLVED: To nullify wasteful man-hours and time for replacement, rearrangement, etc., by establishing a **seal** of a rotary **shaft** bearing part effectively and properly in the high speed rotation at a high temp., for example a hot rolled roll bearing part, preventing wear and denaturation of the **sealing** material and leakage of lubricating oil, and thereby enhancing the durability.

SOLUTION: A **seal** mechanism is to be fitted in a neck part between the body 2 of a roll and a **shaft**, and is composed of an elastic **seal** member 1, a fixing part 3 confronting **lip** parts 11 and 12 installed opposingly on the elastic **seal** member 1, and an inner ring 4 and taper **sleeve** 5 formed opposingly on the two sides of the **seal** member 1. The middle part and/or the joining end part of the **lip** parts 11 and 12 opposing so as to join with the fixing frame 3 on the two sides of the frame 3 are made in thinner wall gradually, and a groove as oil sump is formed at the forefront of the joint.

COPYRIGHT: (C)1999,JPO

C:\Program Files\Dialog\DialogLink\Graphics\4B.bmp

